

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>B02C</b>		<b>A2</b>	(11) International Publication Number: <b>WO 99/46049</b>
			(43) International Publication Date: 16 September 1999 (16.09.99)
(21) International Application Number: <b>PCT/NZ99/00030</b>		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 12 March 1999 (12.03.99)			
(30) Priority Data: 329800 13 March 1998 (13.03.98) <b>NZ</b>			
(71) Applicant (for all designated States except US): <b>ROCKTEC LIMITED [NZ/NZ]; Mangawhero Road, Matamata 2271 (NZ).</b>			
(72) Inventor; and (75) Inventor/Applicant (for US only): <b>ROBSON, Angus, Peter [NZ/NZ]; Watson Road, Te Poi, Matamata 2270 (NZ).</b>		<b>Published</b> <i>Without international search report and to be republished upon receipt of that report.</i>	
(74) Agents: <b>SIMS, Anthony, W. et al.; 29 Clarence Street, P.O. Box 759, Hamilton 2001 (NZ).</b>			
(54) Title: <b>IMPROVEMENTS TO ROCK CRUSHERS</b>			
(57) Abstract <p>The invention relates to improvements to rock crushers, and in particular rotary impact rock crushers. The crushing chamber may be angled to achieve the desired rock product. Also disclosed is an anvil for use in a crusher whereby the anvil position is adjustable. The invention enables the operator to dial up a particular rock product specification by adjusting the angle of the crushing chamber and/or the position of the anvil. The adjustments may be made without ceasing the operation of the machine. Improved control over fracture mechanisms within the crushing chamber and as a consequence the rock product, are achievable with the present invention.</p>			